

### PROLITE

This class of motorcycle requires an MNZ Homologation, with a minimum of 50 units sold of that mass produced motorcycle.

This homologated motorcycle must be a street type, road registerable and Wof mass production machine, available and sold new in New Zealand.

This class to be called "PROLITE".

In special cases approval may be granted by the Board on an individual basis for a 13 year old to ride in this production class. The basis for this approval will be a recommendation from a previous or current top level rider or coach who shall commit to act as a mentor to the junior rider until the rider is eligible for a senior license. All riders are to wear a high visibility vest over their leathers for the first events at which they compete. Proof of these events will be from their log book.

#### NOTE:

All items not mentioned in the following articles must remain as originally produced by the manufacturer, remain fitted and operational for that homologated model. The parts and service manuals for the homologated models will be used as reference to confirm standard specifications.

1. Twin and single cylinder four stroke engines from 200cc up to 250cc standard engines.
2. Only OEM engine parts for the homologated model may be fitted - In the case of overboring, only oversizes listed as genuine options in the manufacturers partsbook for the homologated model may be used. only gaskets of the standard thickness may be used
3. Number Plate Colours and placement:  
Prefer to rule 10.2.3
4. Fuel  
This class must function on normal unleaded fuel with a maximum lead content of 0.013g/l (unleaded) and a maximum RON of 98.
5. Tyres
  - a) Only treaded tyres on sale to the general public in New Zealand as E or DOT marked road legal type treaded, all weather fitment will be permitted.
  - b) No specialist rain / wet tyres allowed, even if E or DOT marked. No modification or treatment of the tread or carcass is permitted
  - c) Front and rear tyre sizes fitted must conform to the tyre Manufacturers specifications for the rim sizes fitted to that homologated model.
  - d) Tyre warmers are not allowed.
6. Machine Specifications (General)  
All machines must comply with the relevant general competition Rules such as Chapter 10.

## 7. Modifications Allowed

- a) All front fork internals must remain as originally supplied by the machines manufacturer. Quality and quantity of the oil in forks is free to change.
- b) The height and position of the front fork in relation to the top yoke (fork crown) is free.
- c) Muffler: Slip-on Alloy or Stainless steel only, original headers must be retained.
- d) Drive sprockets and chain width may be changed
- e) Handlebars and levers may be changed, but the height and angle of the bars must remain as standard.
- f) Instrument panel aftermarket items may be substituted for Tacho/Speedo and temperature gauges
- g) Foot rest/Foot controls, must be mounted to the frame at the original mounting point and be the same height and position as standard.
- h) Substitution of rubber topped foot pegs for other material is allowed.
- i) The fitment of an aftermarket sub frame supporting the seat and tailpiece is allowed providing that the construction is as the original OEM parts both in material, construction and design. Items (battery, wiring, ecu, etc) must be fitted to the aftermarket Sub frame in the same position as the original OEM fitment.
- j) Small protective cones/knobs may be fitted to minimize accident damage.
- k) Brake disc pads.
- l) Brake lines front and rear.
- m) Spark plugs
- n) Carburettor jetting and slides. Fuel injected models may run model specific" plug and play, Power Commander type" mixture controllers.  
NO other modifications/ alterations/ additions to fuel mixture control, ignition curves or wiring loom are allowable
- o) Ignition, Engine control module/unit (ICM, ECU, ECM) and wiring loom must remain standard.
- p) **Countershaft sprocket cover may be modified to allow for altered gear change pattern, but must remain fitted to the machine.**
- q) **Lambda sensor(s) may be removed and replaced with a blanking plug, but the original fitting must remain in the original unmodified header.**

## 8. Fairing/Body Work

- a) Fibreglass replicas of originals are allowed but the fairing shape and size must remain as homologated.
- b) Headlight, mirror and indicator holes may be filled in. Note that the use of carbon fibre is restricted to small reinforcing amounts in the mounting area only.
- c) The fairing blade may be replaced with a replica item, but must be the same height and shape as originally fitted.
- d) Replicas of genuine OEM solo seat cowls for that homologated model may be fitted

- e) The original combination instrument/fairing brackets may be changed.
9. The following items must be removed
- a) Passenger footrests/grab rails
  - b) Side stand
  - c) Safety bars, centre stands (all fixed or welded brackets must remain in place)
  - d) Where breather or over flow pipes are fitted they must discharge via existing outlet. The original closed system must be retained; no direct atmospheric emission is permitted.
  - e) Headlight, rear light and blinkers must be removed
  - f) Horn
  - g) License plate bracket
10. Additional Equipment not fitted on the original homologated model must not be added (ie Data Acquisition, computers, recording equipment etc) Lap timers may be used.
11. The following may be removed
- a) Instruments, brackets and associated cables
  - b) Toolbox
  - c) Speedometer
  - d) Radiator fan and wiring
  - e) Number plate/ rear guard
  - f) **Passenger footpeg brackets may be unbolted only – NO cutting allowed. In cases where the peg hanger is used as a muffler bracket, it may be replaced with an alternative of the same material or heavier**
12. Items not allowed
- a) No Data logging
  - b) The fitment of aftermarket Traction Control units is not permitted